

APOLLO fish grader XL8, XL10

Data's for APOLLO XL-3m:

Number of tracks : 8 or 10 tracks

Roller diameter : $\varnothing 89\text{mm}$

Grading length : 3 mtr.

Grading range : 2-45mm, 12-55mm or 22-65mm

Outlets (grading sizes) : 3 or 4 pcs., diameter $\varnothing 200\text{mm}$ - reversible

Supply : single phase 230V, three phases 230V or 400V



Maskinfabrikken APOLLO A/S

Industrivej 2 • 7330 Brande • Denmark

Tel. +45 97180690 • www.apollo.dk

Technical data, XL8 and XL10

| Type | XL8 S | XL8 M | XL8 L | XL10 S | XL10 M | XL10 L |
|--------------------------------------|-------------|--------------|--------------|-------------|--------------|--------------|
| Number of tracks | 8 | 8 | 8 | 10 | 10 | 10 |
| Grading distance [mm] | 2-45 | 12-55 | 22-65 | 2-45 | 12-55 | 22-65 |
| Min. distance of topbars [mm] | 57 | 67 | 77 | 57 | 67 | 77 |
| Grading length [mm] | 3000 | 3000 | 3000 | 3000 | 3000 | 3000 |
| Width of machine at top [mm] | 1890 | 1970 | 2050 | 2340 | 2440 | 2540 |
| Total width [mm] | 2100 | 2180 | 2260 | 2550 | 2650 | 2750 |
| Total length, ex. sep. [mm] | 4270 | 4270 | 4270 | 4270 | 4270 | 4270 |
| Max. height [mm] | 1750 | 1750 | 1750 | 1750 | 1750 | 1750 |
| Height adjustment, front [mm] | 260 | 260 | 260 | 260 | 260 | 260 |
| Weight ex. sep. [kg] | 900 | 950 | 1000 | 1100 | 1150 | 1200 |
| Motor power [kW] | 0,25 | 0,25 | 0,25 | 0,25 | 0,25 | 0,25 |
| Motor rpm. [rpm] | 1400 | 1400 | 1400 | 1400 | 1400 | 1400 |
| Standard voltage [V] | 230/400 | 230/400 | 230/400 | 230/400 | 230/400 | 230/400 |
| Number of grading sizes | 3 or 4 | 3 or 4 | 3 or 4 | 3 or 4 | 3 or 4 | 3 or 4 |
| Min. spray water [m ³ /h] | 8 | 8 | 8 | 10 | 10 | 10 |
| Size range (salmon) [gr] | 5-900 | 50-1400 | 220-1800 | 5-900 | 50-1400 | 220-1800 |



Maskinfabrikken APOLLO A/S

Industrivej 2 • 7330 Brande • Denmark

Tel. +45 97180690 • www.apollo.dk